

# Water bath "Aquaterm"

ADJUSTABLE TEMPERATURE FROM 30 °C TO 110 °C. STABILITY ±2 °C.

## **Economic option**

### **FEATURES**

AISI 304 stainless steel tank with epoxy coated base.

Heater element embedded in high temperature, corrosive resistant INCOLOY.

### **CONTROL PANEL**

Temperature regulator thermostat switch, synchronised with an indicator lamp.

Part No.	Capacity	Ø	Height	Ø Height	Power	Weight
	litres	(usable)	cm	(exterior) cm	W	Kg
3000916	1.5	20	11.5	22 20.5	640	1.3



ACCESSORIES IN AISI 304. STAINLESS STEEL

Perforated shelf.
Part No. 6000998

Flat Lid with 5 concentric ring set.

Part No. 3000917



# **Boiling bath "Baher"**

lack adjustable temperature from 30 °C to 110 °C. Stability  $\pm 3$  °C.

#### **FEATURES**

Rapid boiling (6-7 minutes).

AISI 304 stainless steel tank and epoxy coated base.

Heater element embedded in INCOLOY stainless steel.

#### **CONTROL PANEL**

Temperature regulator thermostat switch, synchronised with an indicator lamp.

Part No.	Capacity	Ø	Height	Ø Height	Power	Weight
	litres	(usable)	cm	(exterior) cm	W	Kg
70005/10	1	1/1	11	15 10	6/10	1



### **ACCESSORIES MADE OF STAINLESS STEEL**

**Lid** with bakelite handle. **Rack** 24 haemolysis tubes up to 13 mm diameter. Part No. 7000572 Part No. 7004002

**Rack** for 24 tubes up to 18 mm diameter. Part No. 7000541 **Perforated shelf.** Part No. **6001194** 



## Water and oil baths "Univeba"

WATER BATH: ADJUSTABLE TEMPERATURE FROM AMBIENT +5 °C TO 110 °C STABILITY  $\pm 2$  °C. OIL BATH: ADJUSTABLE TEMPERATURE FROM AMBIENT +5 °C TO 200 °C STABILITY  $\pm 3$  °C.

### **SAFETY:**

CONFORMS TO THE DIN STANDARD 12877 BY INCORPORATING A MANUALLY RESET OVER TEMPERATURE SAFETY CUT-OUT.

# APPLICATIONS To be used with a

To be used with a rotary evaporator or as a stand alone Bains Marie bath.

### **FEATURES**

Tank interior and exterior case made of AISI 304 stainless steel. The heater element is embedded in a protective INCOLOY stainless steel shield.

### **CONTROL PANEL**

Illuminated main power switch indicator lamp. Hydraulic temperature thermostat regulator synchronised with an indicator lamp. Safety thermostat cut out indicator lamp.



### **MODELS**

Part No.	Maximum Temperature °C	Capacity litres	Ø Height (usable) cm		Height / Widht / Depth (exterior) cm			Power W	Weight Kg
3000400	110	2.5	18	13	19	22	27	390	4
3000401	200	2.5	18	13	19	22	27	640	4

### **ACCESSORIES MADE OF STAINLESS STEEL**

- 1- Heating element cover shelf.
  Part No. 6000033
- 2- Reduction ring cover lid of 110, 80, 60 and 37 mm Ø. With a thermometer location hole in the lid. Part No. 7004001
- **3- Tube rack** for 24 haemolysis tubes up to 13 mm Ø. Part No. **7004002**
- **4- Tube support** rack for 24 tubes up to 18 mm Ø. Part No. **7000541**
- 5- Thermometer. Part No.

**1000120** up to 120 °C. **1000873** up to 220 °C.